JMC-7110

JMC-7110

		LGA1151 Gen 6th/7th/8th/9th Core™i3/i5/i7Pentium /Celeron Processor
		Q170/H110
	BIOS	AMI UEFI BIOS
		2x DDR4 2133/2400 MHz SO-DIMM, up to 32GB
		7th Gen. CPU: Windows 10 6th Gen. CPU: Windows 10, Windows 8 .1, Windows 7 Linux OS
I/O	USB	Q170: 8x USB3.0, 2x USB2.0(Internal), 1x USB dongle(Internal) H110: 4x USB3.0, 4x USB2.0, 1x USB2.0(Internal)
I/O	COM	2x RS232(4)/422/485 ( ),2x RS232/422/485+2x RS-232( )
I/O	LED	1xPower, 1xHDD
	Mini-PCIe	Q170: 2x Mini-PCIe (SIM , 4G 1 mSATA) H110: 1x Mini-PCIe (SIM , 4G , 1x mSATA
	Graphics Processor	Intel®UHD Graphics 530/510
	Interface	HDMI 2nd/DP/DVI 1xVGA, VGA 1920*1200@60Hz 1xHDMI,HDMI 4096*2160@24Hz
	Storage Device	2 x 2.5”HDD/SSD(1) Q170 SATA RAID 0/1, 1 x mSATA
	Audio IC	Realtek ALC897
	Audio Interface	1xMic-in, 1xLine-out
	LAN IC	1xI219LM, 1x I210AT
	Interface	2xRJ45
	Power Input	DC IN 9~36V
	Power Interface	4-Pole Phoenix DC plug in
	Watchdog Timer	1 to 255 sec./m per step
	TPM	
	Dimensions	230mm(W)×192mm(D)×88mm(H)
	Weight	3.53K
	Mounting	Desk/Wall-mounting
	Operating Temp.	65W -10 ~50 , 35W -10 ~60
	Storage Temp.	-40~85
	Humidity	95%@40
	Shock	With SSD: 15G, IEC 60068-2-27, half sine, 11ms duration
	Vibration	With SSD:2Grms, IEC 60068-2-64, random 5~500Hz 1 hr/axis With HDD:1Grms, IEC 60068-2-64, random 5~500Hz 1 hr/axis

		DIMM	LAN	USB 3.0	USB 2.0	COM	2.5” SSD/HDD	mPCIe/ mSATA
JMC-7110Q	Q170							

所有产品规格如有更改，不

■ I/O)

301800019433 (HDMI 301800012515 (Switch) 302300018777(_)	HDMI Remote power on/off module
301800012079 (COM) 302300018731(1xDB9 _) 302300018735(1xDB9 _) 302300018746(2xDB9 _)	COMport kit module
301800012513 _DB9 301800015453 _DB25 302300018779 (5 _DB25)	GZ0 <